

TVT

secure the world with you

HDCCTV
Over Coax



CE FC RoHS

TD-2732TD-PL

TD-2732TD-PL

1080P HD TVI DVR



**1080P DISPLAY
1080P RECORD
1080P PLAYBACK**

HIGH QUALITY, GREATER RELIABILITY & DIVERSITY OF PRODUCT LINE
STRENGTHEN YOUR SECURITY

HI
HAMS
INDIA

DISTRIBUTOR AND SERVICE PARTNERS IN INDIA | SUPPORT: +91-11-41576969 | EMAIL: SUPPORT@TVTINDIA.COM | WWW.TVTINDIA.COM

secure the world with you





Specification

Model		TD-2732TD-PL
System	Compression	Standard H.264 High Profile
	CPU	Cortex A9
	OS	Embedded Linux
Video	Input	BNC × 32 Support TVI 1080P@25 / 30fps, 720P@25 / 30 / 50 / 60fps and AHD 1080P@25 / 30fps, 720P@25 / 30fps, WD1 input
	Output	HDMI × 1 : 1920 × 1080 VGA × 1 : 1920 × 1080
Audio	Input	RCA × 16
	Output	RCA × 1
	2-way audio	RCA × 1
Record	Resolution	1080P: 1920 × 1080, 720P : 1280 × 720, WD1
	Frame Rate	720P / WD1 800 fps (PAL) / 960 fps (NTSC)
		1080P 400 fps (PAL) / 480 fps (NTSC)
	Bit rate	768Kbps ~ 8Mbps
	Encode	VBR / CBR
	Quality	6 Level
	Mode	Manual, timer, motion, sensor
Play back	File manager	Lock, unlock
	Playback	8 CH
	Search	Time / calendar search, event (motion, external alarm)
	Smart Search	Highlighted date and time to display the channel record
	Function	Play, pause, FF, FB, digital zoom
Alarm	Mode	Sensor, motion, video loss
	Input	16 CH
	Output	4 CH
	Triggering	Record, PTZ move, alarm out, e-mail, etc
Network	Interface	RJ45 10M / 100M / 1000M × 1
	Protocol	TCP / IP, UDP, DHCP, DNS, PPPOE, DDNS
	Others	Up to 10 online users , dual stream
Cell phone	OS	iPhone, Andriod
	Function	Multi-screen surveillance (for certain model) , record, snapshot, PTZ control, save the device list
I / O	HDD	SATA × 8, e-SATA × 2
	RS485	RS485 × 2, one for PTZ, another for keyboard
	USB	USB 2.0 × 2, one for mouse, another for USB backup device
	IR controller	Yes
Others	Power supply	ATX
	Consumption	< 40W (without HDD)
	Dimensions (mm)	430 × 450 × 90 (W × D × H)
	Work Environment	- 10 °C ~ 50 °C , 10 % ~ 90 % Humidity

Introduction

TD-2732TD-PL series are standard 32 CH 1080P high resolution DVRs, which adopt the standard H.264 high profile compression format and the most advanced SOC technique to ensure recording in each channel and realize outstanding robustness of the system. TD-2732TD-PL support 32 CH video input, 16 CH audio input, simultaneous 8 CH playback. The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.

Characteristics

- 32 CH HD video input, 1080P / 720P / WD1 recording
- Adopt standard H.264 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor
- Playback: 8 CH simultaneously playback
- Search: time / calendar, events (alarm, motion)
- Express and flexible backup via USB and network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE Network protocol, IE browse and CMS supported
- Remote control via IE or CMS: preview, playback, backup, PTZ and configuration
- Support dual stream technology to encode recording stream and network stream separately; network stream can be adjustable to fit bandwidth without changing recording quality
- Multi-user online simultaneously
- Authorization management, log review and device status review
- HDMI 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 128 presets and 8 cruises
- Powerful smart phone surveillance supporting iPhone, Andriod
- Support NAT function, support QR code scanning by mobile phone
- Complete SDK software available, easy to integrate with other applications

Dimensions

