

CP- VNC-D21R3**2 MP Full HD Array Dome Camera - 30Mtr.****INDIGO****Main Features**

- 1/2.7" 2MP PS CMOS Image Sensor
- Max 25/30fps@1080P
- Ultra 265,H.265,H.264,MJPEG Triple-stream Encoding
- DWDR, Day/Night (ICR), 2D/3D-DNR, ROI, AWB, AGC, BLC
- 2.8mm lens (3.6mm optional)
- IR Range of 30 Mtrs, IP67, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS

**InstaStream****CE FC** **RoHS**
COMPLIANT

CP- VNC-D21R3

2 MP Full HD Array Dome Camera - 30Mtr.



Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Lens
 Gain Control (AGC)
 S/N Ratio
 Back Light Compensation
 Angle of View
 Video Compression
 Video Streaming
 Resolution
 Frame Rate
 Motion detection
 Privacy Mask
 ICR
 ROI
 Protocol
 Ethernet
 IR
 OSD
 Weatherproof Standard
 Operating Temperature
 Humidity
 Power Source
 Power Consumption
 Dimension
 Weight

Specification

1/2.7" 2MP Progressive scan CMOS
 Colour: 0.02 Lux (F2.0, AGC ON) 0 Lux with IR
 Auto/Manual, 1~1/100000 s
 Auto/Manual
 2.8mm (3.6mm Optional)
 Auto/Manual
 >52dB
 BLC / HLC / DWDR
 2.8mm- 112.7°(H), 60.1°(V), 146.5°(O), 3.6mm- 86.5°(H), 44.1°(V), 106.4°(O)
 H.265, H.264, MJPEG
 Triple
 1920x1080
 Main Stream: 1080P (1920x1080), Max 30fps; Sub Stream: 720P (1280x720), Max 30fps; Third Stream: CIF (352x288), Max 30fps
 Up to 4 areas
 Up to 8 areas
 IR-cut filter with auto switch (ICR)
 Up to 2 areas
 IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS, ONVIF (Profile S, Profile T), API
 10M/100M Base-TX Ethernet
 IR Range of 30 Mtr.
 Up to 4 OSDs
 IP67
 -30°C ~ 60°C (-22°F ~ 140°F)
 ≤ 95% RH (non-condensing)
 12 V DC, or PoE (IEEE802.3 af)
 Max 5.0W
 Ø118 x 96 mm (Ø4.6" x 3.8")
 0.3kg

