

CP- UNC-VH31ZL5-VMD**3 MP Full HD WDR IR Vandal Dome Camera - 50Mtr.****Main Features**

- 1/2.8" 3MP PS CMOS Image Sensor
- Max 25/30fps@3MP
- Support H.265/H.264/MJPEG dual codec
- WDR (upto 140dB), Day/Night (ICR), 3D-DNR, AWB, AGC, BLC
- 2.8 ~12mm varifocal motorized lens
- IR Range of 50 Mtrs, IP67, IK10, PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-VH31ZL5-VMD

3 MP Full HD WDR IR Vandal Dome Camera - 50Mtr.



Feature

Image Sensor
Minimum Illumination
Effective Pixels
Shutter Speed
White Balance
Gain Control (AGC)
Lens
Video Compression
Back Light Compensation
S/N Ratio
Video Streaming
Resolution
Video Output
Privacy Mask
ICR
ROI
Audio Input
Audio Compression
Audio Output
Alarm IN
Alarm Out
Bit Rate
Protocol
Smart Detection
Ethernet
User Account
Smart Phone
IR

Specification

1/2.8" 3MP Progressive scan CMOS
0.005Lux/F1.4(Color), 0Lux/F1.4(IR on)
2048(H) x 1536(V)
Auto/Manual, 1/3(4)~1/100000s
Auto/Sunny/Night/Outdoor/Customized
Auto/Manual
2.8-12mm motorized
H.265/H.264 / MJPEG
BLC/ HLC/ WDR(140dB)
More than 50dB
Main Stream:3M/1080P (1~25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps), Third Stream: 1080P/720P/D1(1 ~ 25/30fps)
3M(2048x 1536)/1080P(1920x 1080) / 720P(1280x 720) /D1(704x 576) /CIF(352x 288)
1 port
Up to 4 areas
Auto (ICR)/Color/B/W
Up to 4 areas
1 Channel
G.711a / G.711u/AAC
1 Channel
2 Channel In
1 Channel Out
H.264: 40K ~ 10Mbps
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF, PSIA, CGI
Tripwire, Intrusion, Scene Change, Missing/Abandoned, Audio detect, Face detect, People counting, Heat map
RJ-45 (10/100Base-T)
20 Users
iPhone, iPad, Android Phone
IR Range of 50 Mtr.



CP- UNC-VH31ZL5-VMD

3 MP Full HD WDR IR Vandal Dome Camera - 50Mtr.



Feature

Micro SD
Operating Temperature
Power Source
Power Consumption
Weatherproof Standard
Dimension
Weight

Specification

Max 128GB
-30°C~+60°C , Less than 90%RH
DC12V(AC24V optional), PoE (802.3af)
Max 12W
IP67 & IK10
Φ159mm × 117.9mm
0.8 Kg.