

CP- VNR-3209**9 Ch. Network Video Recorder****Main Features**

- 9 Channel IP Camera Input
- Support Ultra 265/H.265/H.264 Video Formats
- Support Up to 8 Megapixels resolution recording
- 160Mbps Incoming/ 72Mbps Outgoing Bandwidth
- Support 2 SATA HDDs up to 10TB Each, 2 USB Ports
- Support HDMI and VGA simultaneous output
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



CP- VNR-3209

9 Ch. Network Video Recorder

Feature

Processor
 Operating System
 IP Camera Input
 Two-way Talk
 User Interface

 HDMI/VGA Output

 Compression
 Recording Resolution
 Video Recording
 Audio Output
 Live view/Playback
 Corridor Mode Screen
 Hard Disk
 Capability
 Playback
 Interface Ports
 Max User Account
 Ethernet
 Protocols
 Power Supply
 Power Consumption
 Working Temp
 Working Humidity
 Dimensions
 Weight

Specification

Dual-core embedded processor
 Embedded LINUX
 9 channel
 1 channel, RCA
 GUI

 HDMI: 4K (3840x2160)@30, 1920x1080p@60, 1920x1080p@50, 1600x1200@60,
 1280x1024@60, 1280x720@60, 1024x768@60,
 VGA: 1920x1080p@60, 1920x1080p@50, 1280x1024@60, 1280x720@60, 1024x768@60

 Ultra 265, H.265, H.264
 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 160 Mbps
 1 channel, RCA
 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 3/4/5/7/9
 2 SATA ports, up to 10 TB Each
 1 x 4K@30, 1 x 6MP@30, 1 x 5MP@30, 2 x 4MP@30, 2 x 3MP@30, 4 x 1080p@30,
 8 x 720p@30
 9 Channel
 2 USB Ports
 128
 1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
 P2P, UPnP, NTP, DHCP, PPPoE, ONVIF (Profile S, Profile G, Profile T)
 12V DC
 ≤ 7 W (without HDD)
 -10°C ~ + 55°C (+14°F ~ +131°F)
 ≤ 90% RH (non-condensing)
 380 mm x 315mm x 49 mm
 ≤ 1.6 Kg (without HDD)