

CP- VNR-3116**16 Ch. 4K Network Video Recorder****Main Features**

- 16 Channel IP Camera Input
- Ultra 265/H.265/H.264 Video Formats
- Support 4K Resolution Upto 8MP Recording
- 80 Mbps Incoming/Outgoing Bandwidth
- Support 1 SATA HDDs up to 10TB, 3 USB Ports
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



CP- VNR-3116

16 Ch. 4K Network Video Recorder

Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
HDMI/VGA Output
Compression
Recording Resolution
Video Recording
Live view/Playback
Capability
Corridor Mode Screen
Video Display Split
VCA Detection
VCA Search
Statistical Analysis
Audio Input
Audio Output
Alarm Input
Alarm Output
Hard Disk
Playback
Interface Ports
Max User Account
Ethernet
Protocols

Specification

Dual-core embedded processor
16 channel
Embedded LINUX
1 channel, RCA
GUI
HDMI: 4K(3840x2160)/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Ultra 265/H.265/H.264
8MP, 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
80Mbps
8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
1 x 4K@30, 2 x 4MP@30, 4 x 1080p@30, 8 x 720p@30, 16 x D1
3/4/5/7/9
1/4/8/9/16
Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking
Face search, Behaviour search
People counting
1 channel, RCA
1 channel, RCA
4 channel
1 channel
1 SATA ports, up to 10TB
16 Channel
3 USB Port
128
1 RJ-45 10M/100M Self-adaptive Ethernet Interface
P2P, UPnP, NTP, DHCP, PPPoE, ONVIF conformance: Profile S, Profile G, Profile T

 **CP- VNR-3116****16 Ch. 4K Network Video Recorder****Feature**

Power Supply
Power Consumption
Working Temp
Working Humidity
Dimensions
Weight

Specification

12V DC
≤ 8 W
-10°C ~ + 55°C (+14°F ~ +131°F)
10% ~ 90%
44 x 260 x 240mm (1.7" x 10.2" x 9.4")
≤ 1.12 Kg