

### CP-UNR-4K632R8-V2

### 32 Ch. H.265+ 4K Network Video Recorder

- Up to 32 channel IP camera input
- Up to 12MP resolution preview and playback
- Max 384Mbps incoming bandwidth
- Support 8 SATA HDDs up to 10TB Each, 4 USB Ports (2 USB3.0), 1 eSATA port
- 2 HDMI / 1 VGA simultaneous video output
- Support Multi-brand network cameras
- Support RAID 0/1/5/6/10
- Smart Tracking and Intelligent Video
- ONVIF Version 2.4 conformance
- · Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro















#### **System Overview**

This product is perfect for IP video surveillance around the globe as it uses a highly-efficient recording technology that brings to you the premium quality recordings. The 4K resolution present in this NVR helps in focusing on every minute detail in the image for critical activities such as identification of people and vehicles. On top of all that, this NVR comes with a mouse shortcut operation menu which lets you remotely manage and control the entire system. All of these functions make this NVR the best choice for a number of applications ranging from public safety, transportation stations to government and private institutions as well as city centers and shopping malls.

#### **Functions**

#### N+M Hot Standby

Understanding the need of the hour, this NVR has been crafted through using the greatly-reliable redundant N+M Hot Standby design which presents a secure, failsafe way of ensuring immediate backup of the video from your security solution.







# THINK SECURITY THINK CP PLUS





## CP-UNR-4K632R8-V2

32 Ch. H.265+ 4K Network Video Recorder

#### **Functions**

#### RAID 0/1/5/6/10

Offering a balance between storage performance, storage capacity, and data integrity, the NVR features Fruitfull RAID 0/1/5/6/10 for faster and safer recording.

#### **ANR Technology**

The automatic network replenishment technology has eased conducting surveillance manifolds by automatically storing the video data on an IP Camera SD card when the network is disconnected to prevent losing the video feed even for a single second. And so, whenever the network has been recovered next, the data is automatically transferred to the NVR.

#### **4K Resolution**

Created ideally for covering every inch of the space that is under surveillance, the 4K resolution technology lets you enjoy complete clarity in a magnified image. This technology has proven to be the most beneficial for image processing because it provides four times the better resolution of a standard HDTV 1080P Camera.

#### gCMOB/ iCMOB

Designed to allow users to access and control live streaming from CP PLUS IP Cameras, DVRs/ NVRs and Video Door Phones, the CP PLUS gCMOB/ iCMOB application offers a host of features such as Easy GUI, up to 16 live viewing split-ups; InstaOn cloud support; Playback; digital zoom ins; two-way talk, and more.

#### **KVMS Pro**

The KVMS Pro is a hybrid security management software that allows the management of various surveillance devices such as cameras, DVRs/ NVRs, encoders/ decoders, etc. It is released with the surveillance hardware and exclusively supports CP PLUS devices.

#### About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.









## CP-UNR-4K632R8-V2

32 Ch. H.265+ 4K Network Video Recorder

| Feature                | Specification   |
|------------------------|---|
| Processor              | Intel Dual-core Processor   |
| IP Camera Input        | 32 channel  |
| Operating System       | Embedded LINUX  |
| Two-way Talk           | 1 channel Input, 1 channel Output, RCA  |
| User Interface         | GUI   |
| Video Output           | 2 HDMI (up to 3840× 2160), 1 VGA  |
| Compression            | Smart H.265+/H.265/Smart H.264+/H.264/MPEG4/MJPEG   |
| Video Resolution       | 3840× 2160, 1920× 1080, 1280× 1024, 1280× 720, 1024× 768                                  |
| Video Recording        | 384Mbps   |
| Video Display Split    | The 1st screen: 1/4/8/9/16/25/36, The 2nd screen: 1/4/8/9/16                              |
| Resolution             | 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P etc.                                    |
| OSD                    | Camera title, Time, Video loss, Camera lock, Motion detection, Recording                  |
| Motion Detection       | MD Zones: 396(22×18).   |
| Video Loss             | Supports  |
| Camera Blank           | Supports  |
| Alarm Input            | 16ch, low level effective, green terminal interface                                       |
| Alarm Output           | 8ch, NO/NC programmable, green terminal interface   |
| Smart Phone            | iPhone, iPad, Android Phone   |
| Hard Disk              | 8 SATA III ports, up to 10TB Each, 1 eSATA port   |
| Trigger Events         | Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips |
| Tracking Trigger Event | Zoom, Tracking, Recording, Preset, Snapshot, Alarm, etc.                                  |
| Bit Rate               | 16Kbps ~ 20Mbps Per Channel   |
| HDD Management         | Single, Raid 0/1/5/6/10 (Support global HDD hot-spare)                                    |
| Hot-Swap               | N/A   |
| Recording Mode         | Manual, Schedule (Regular, MD (Motion Detection), Alarm, IVS), Holiday, Stop              |
| Search Mode            | Time/Date, Alarm, MD & Exact search (accurate to second)                                  |







# THINK SECURITY THINK CP PLUS



| Feature           | Specification   |
|-------------------|---|
| Playback          | 128Mbps in Raid 5 mode, 64Mbps in single HDD mode   |
| Backup Mode       | USB Device/Network/eSATA Device   |
| Interface Ports   | 4 USB ports(2 USB2.0, 2 USB3.0), 1 RS485, 1 RS232   |
| Max User Account  | 128 users   |
| Record Interval   | 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  |
| Ethernet          | 2 RJ-45 port (10/100M/1000Mbps)   |
| Protocols         | HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search, ONVIF Version 2.4, CGI Conformant |
| Power Supply      | AC100V ~ 240V, 50 ~ 60 Hz   |
| Power Consumption | <20W (Without HDD)  |
| Working Temp      | -10 ~+55°C / 10~90%RH / 86~106kpa   |
| Dimensions        | 440mm x 451.08mm x 94.85mm  |
| Weight            | 9kg (without HDD)   |







### Dimensions (mm/inch)





