

CP- UNR-4K4324-V2**32 Ch. H.265+ 4K Network Video Recorder****Main Features**

- Up to 32 channel IP camera input
- Smart H.265+/Smart H.264+ codec decoding
- Up to 8MP resolution preview and playback
- Max. 200Mbps incoming and 96Mbps outgoing bandwidth
- Support 4 SATA HDDs up to 10TB each, 2 USB(1 USB3.0)
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNR-4K4324-V2

32 Ch. H.265+ 4K Network Video Recorder

Feature

Processor
 IP Camera Input
 Operating System
 Two-way Talk
 User Interface
 Video Output
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Motion Detection
 Video Loss
 Camera Blank
 Audio Compression
 Alarm Input
 Alarm Output
 Hard Disk
 Decoding Capability
 Smart Phone
 Trigger Events
 Recording Mode
 Search Mode
 Multi-channel Playback
 Playback Function
 Backup Mode
 Interface Ports
 Max User Account
 Record Interval
 Ethernet

Specification

Industrial embedded micro-processor
 32 channel
 Embedded LINUX
 1 channel Input, 1 channel Output, RCA
 GUI
 1 HDMI, 1 VGA
 Smart H.265+/H.265/Smart H.264+/H.264
 3840×2160, 1920×1080, 1280×1024, 1280×720, 1024×768
 Max. 200Mbps Incoming and 96Mbps outgoing bandwidth
 1/4/8/9/16/25/36
 MD Zones: 396(22×18).
 Supports
 Supports
 PCM; G.711A; G.711U; G.726
 16 Channel, Low Level Effective, Green Terminal Interface
 4 Channel, NO/NC Programmable, Green Terminal Interface
 4 SATA III ports, up to 10TB Each
 8 channels@1080p (30fps)
 iPhone, iPad, Android Phone
 Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips
 Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Tampering, Video Loss), Stop
 Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
 1/4/9/16
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
 USB Device/Network
 2 USB (1USB 3.0), 1 RS485, 1 RS232
 128 users
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet ports



CP- UNR-4K4324-V2**32 Ch. H.265+ 4K Network Video Recorder****Feature**

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

HTTP; HTTPS; TCP/IP; IPv4/IPv6; UPnP; SNMP; RTSP; UDP; SMTP; NTP; DHCP; DNS; IP Filter; DDNS; FTP; Alarm Server; IP Search, P2P, ONVIF (profile T/S/G); CGI; SDK

AC 100~240V, 50/60 Hz

<13.7W (Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm x 411.1mm x 76mm

4.7kg (without HDD)