✕ CP PLUS

CP- VNR-3F64B-R

64 Ch. H.265 Network Video Recorder

Main Features

- 64 Channel IP Camera Input
- Support Ultra 265/H.265/H.264 video formats
- Up to 12 Megapixels Resolution Recording
- 320Mbps Incoming/ Outgoing Bandwidth
- Various fisheye dewarping modes for live view and playback for both web interface and GUI
- Support HDD hot swap with RAID 0, 1, 5, 6, 10,50,60 storage scheme configurable
- Support 16 SATA HDDs up to 10TB Each, 3 USB Ports
- Support 2-ch HDMI, 1-ch VGA, HDMI2 at up to 4K(3840x2160) resolution
- Support Multi-brand network cameras
- Support N +1 Hot spare
- Mobile Software: Android, iOS
- CMS Software: IVMS

64 Ch | Linux POWERED | H.265 COMPRESSION | HI-SPEED CERTIFIED USB | GUI | CMS | C E F C | RoHS COMPLIANT

CP- VNR-3F64B-R

64 Ch. H.265 Network Video Recorder

Feature	Specification
Processor	Dual-core embedded processor
IP Camera Input	64 channel
Operating System	Embedded LINUX
User Interface	GUI
Video Output	HDMI1/VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz HDMI 2: 4K (3840x2160)/60Hz, 4K (3840x2160)/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Compression	Ultra 265, H.265, H.264
Video Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/960H/D1/2CIF/CIF
Video Recording	320Mbps
Video Display Split	1/4/8/9/16/25/36
Audio Input	1 channel, RCA
Audio Output	1 channel, RCA
Smart detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Face search, Behaviour search, People counting
Alarm Input	16 channel
Corridor Mode Screen	3/4/5/7/9/10/12/16
Alarm Output	10 channel
Hard Disk	16 SATA ports, up to 10 TB each, 1 eSATA Port
RAID	RAID 0, 1, 5, 6, 10, 50, 60
Capability	3x12MP@25, 4x4K@30, 8x4MP@30, 16x1080P@30, 32x960P@25, 36x720P@30, 64 x D1
Playback	16 Channel
Interface Ports	3 USB Port, 1 RS485, 1 RS232
Max User Account	128
Ethernet	2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
Protocols	SNMP,P2P, UPnP, NTP, DHCP, PPPoE
Power Supply	100~240 VAC
Power Consumption	≤ 23 W (without HDD)
Working Temp	-10°C ~ + 55°C (+14°F ~ +131°F)
Working Humidity	≤ 90% RH (non-condensing)

CP PLUS

CP- VNR-3F64B-R

64 Ch. H.265 Network Video Recorder

Feature	Specification
Dimensions	482mm ×477mm ×131mm
Weight	≤ 8.19 Kg (without HDD)

CE FC RoHS COMPLIANT