

CP-UD-0209L-4K

Ultra-HD Network Video Decoder

- H.265+/H.265/H.264/MJPEG/MPEG4/MPEG2 video decoding
- Ultra-high decoding ability, up to 12MP
- 2ch HDMI and 2ch DVI-I input, 9ch HDMI output
- Support 1/4/9/16 display split
- Support audio, alarm, bi-directional talk, RS485
- Splicing screens control for zoom/merge/roam/overlay



About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



CP-UD-0209L-4K

Ultra-HD Network Video Decoder

| Feature | Specification |
|------------------------------|--|
| Processor | Embedded processor |
| Operating System | LINUX |
| Video Format | MPEG2/MPEG4/H.264/H.265/H.265+/MJPEG |
| Audio Format | PCM/G711/AAC |
| Decoding Capacity Separately | Port 1,2,3- 3CH@12MP/4CH@4K/16CH@1080P/36CH@720P/48CH@D1 Port 4,5,6 - 3CH@12MP/4CH@4K/16CH@1080P/36CH@720P/48CH@D1 Port 7,8,9 - 3CH@12MP/4CH@4K/16CH@1080P/36CH@720P/48CH@D1 |
| Total Video Decoding | 9CH@12MP/12CH@4K/48CH@1080P/108CH@720P/144CH@D1 |
| Decoding Resolution | 12MP/8MP/6MP/5MP/4MP/3MP/1080P/720P/960H/D1/HD1/2CIF/CIF/QCIF |
| Video Output | 9ch HDMI |
| Display Resolution | 3840×2160/2560×1600/1920×1080/1280×1024/1280×720/1024×768, only 6 ports support 3840×2160, the remaining 3 ports support 2560×1600 |
| Audio Output | 9ch HDMI |
| Communication Interface | 2 RJ45 network port (10M/100M/1000M); 3 RS232(1 DB9, 2 RJ45); 1 RS485 |
| Bi-directional Talk | 1 Pair 3.5mm jack (2.0V Line in/50mV Mic in/10KΩ, 2.0V/16Ω out) |
| Alarm Input | 4ch |
| Alarm Output | 4ch relay out (30VDC 1A, 125VAC, 0.5A) |
| Power Supply | AC100-240V, 50Hz-60Hz |
| Power Consumption | ≤70W |
| Working Temperature | -10 °C to +55 °C (14 °F to 131 °F) |
| Working Humidity | 10~90%RH / 86~106kpa |
| Dimension | 440×408×70mm(17.32 × 16.06 × 2.76 inch), (W x D x H) |
| Weight | 4.83kg |

Dimension (mm/inch)

