

# Automated Parking Barrier Gate BG-100 Grey



## Specification

Maximum length of Boom : 6m  
Boom Rest Stand :Yes  
Arm material : Aluminium  
Time for Up/down : 6s  
Input control signal : Dry contact  
Ingress protection Degree : IP54  
Input Interface for : 1. Photocell  
2. Air switch  
Output interface : lamp  
Optional Interface : Access control panel, Stand alone  
access control,Control button  
Remote control : Yes,upto 25 meters  
Mode : Automatic/Manual  
Incorporated control panel with 3  
push buttons (STOP/UP/Down) to control the motor  
Bumping bounce back : Optional  
Auto closing time : 0-99s  
**Power Supply**  
SMPS - Input: AC 220V / 110V, 50Hz / 60Hz  
Motor power : 90W, 240V AC  
Dimension(mm) : 268 X 348 X 1050  
operating temprature : -20°C to +50°C

## Features

1. Can control by three position switch or by remote control unit, operate 'OPEN', 'CLOSE' and 'STOP'
2. Machine core with compression spring, effectively avoids the accidents caused by spring breaking.
3. Motor cooling fan, solving the problem of heat-protection.
4. Double safety limit switches (Optional)
5. Auto Close function.
6. Manual Release
7. Duty Cycle : intensive
8. MCBF : 30 Lakhs
9. Traffic Light interface. (Optional)
10. Wire control (switch signal)\ Remote control ( upto25m)
11. Compatible with Wigand and RFID Readers.
12. Compatible with bio-metric
13. Die-casting aluminum alloy motor, precision and good at thermal radiating.
14. Support the infrared photocell for anti-bumping function (optional)

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase.

Actual product may differ slightly to that depicted for ongoing product development

[www.esslsecurity.com](http://www.esslsecurity.com)